



X-52

2D MACHINE CONTROL
FOR EXCAVATORS



GX-55 Specifications	
Supply Voltage	9 to 32 VDC
Ports	2x USB Ethernet, RS-232 2x CANBus 2x Digital inputs
Display Panel	640x480 Color VGA, enhanced brightness with analog touchscreen
Operating System	Windows® CE
Operating Temp	-40°C to 70°C
Weight	1.26 kg with backpack 1 kg without backpack
TS-1 Specifications	
Supply Voltage	10 to 30 VDC
Resolution	.01 Degree
Protocol	CAN-Open
Sensor	Solid state, 3-axis, 360
Housing	Powder-coated aluminum
Dust/Humidity	IP67
LS-B10W Specifications	
Detection Range	Vertical: 120mm Horizontal: 270°
On-Grade Zone	2 mm, 6 mm, 12 mm, 30mm
Ports	CAN / Wireless
Dimensions	115 x 40 x 180 mm

2D Excavator System



- Improves job safety
- Work from an existing elevation reference or laser
- Easily upgradable to full 3D solution
- Create, cut, and check complex designs from the cab
- Lightbar grade for visual guidance

2D Excavation essentials

The X-52 is a streamlined and modern excavation system that gets you to grade as a cost effective 2D solution. Our ruggedized LS-B10W laser receiver combined with compact TS-1 tilt sensors lets you stay on grade without having to ever re-string. The GX-55 control box actively guides your bucket where it needs to be and gives you an experience that was designed for your excavating skills. When future projects dictate GNSS location as well as horizontal repeatability, the modern X-52 system is easily upgradeable.

Become one with your work

Today's demand for a safe site is easily answered by incorporating our excavator systems to your daily tasks. We keep field crews out of the hole and optimize digging to save you money and keep schedules on track.

The X-52 excavator system gives you the flexibility to use a wide array of references to work from: existing surface, a hub, a previous cut, or a rotating laser. It's as simple as choosing your reference and entering a cut and/or slope depth for immediate results.

TS-1 Tilt Sensor

Mounted along the bucket, stick, boom, and body for bucket control at any angle.



LS-B10W

Small and lightweight laser receiver for active grade guidance.



For more information:
topconpositioning.com/x-52

Specifications subject to change without notice.
©2016 Topcon Corporation All rights reserved.
7010-2192 A 1/16

